



**THE ULTIMATE BARRIER OF DEFENSE.  
FOR WHATEVER COMES YOUR WAY.**

# BUILDING WRAP



**Install the system. Get a lifetime limited warranty.\***  
TYPAR® BuildingWrap, along with the full TYPAR® Weather Protection System delivers unbeatable coverage.

\*Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at [TYPAR.com/downloads](http://TYPAR.com/downloads) for full details.



# TYPAR® BUILDINGWRAP

## HERE'S HOW WE DEFINE HIGH-PERFORMANCE IN THE INDUSTRY.

TYPAR BuildingWrap excels in all the ways that matter most to true construction pros. For starters, it's rugged—with tear strength that's five times greater than the competition. And while it blocks air and water from getting in, it's smart enough to let moisture out of the wall cavity. That means it stands up to the elements with toughness and intelligence other building wraps can't touch. Plus it delivers incredible durability, efficiency, and safety long after the cladding is up.

## LEADING FEATURES AND BENEFITS:

- Superior water holdout defends the wall cavity
- Exceptional air blockage increases energy-efficiency
- Optimal breathability decreases risk of mold growth
- Extraordinary tear strength prevents worksite damage
- Surfactant resistance reduces hazards of oils, soaps and powerwashing
- UV protection stops rays and provides six months exposure time
- Works with most types of cladding
- Lifetime limited warranty\*

## INSTALL THE SYSTEM. GET A LIFETIME LIMITED WARRANTY.\*

Take your stand on unbeatable—and comprehensive—defense. Our Building Wraps, Flashings, and Construction Tape create the complete TYPAR® Weather Protection System. Install it all together and get covered by the only lifetime limited warranty in the industry.\*

TYPICAL CHARACTERISTICS:	
Basis Weight	Nominal 2.8 osy 21.0 lbs/1000 ft <sup>2</sup>
Thickness	12.9 mils
Hydrostatic Pressure Resistance	>500 cm
Moisture Vapor Transmission Rate	11.7 U.S. perms
Ultraviolet Light Exposure Resistance (UV)	6 months
"Air-Ins" (Air Leakage Test)	.0032L(S.M <sup>2</sup> ) @ 75 pascals
Surface Burning Characteristics (ASTM E84)	
Flame Spread Index	Class A
Smoke Spread Index	PASS

ROLL SIZES:			
5' x 100'	4.5' x 200'	9' x 100'	9.5' x 95'
9' x 150'	9' x 195'	10' x 100'	10' x 150'
10' x 195'			

\*Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at [TYPAR.com/downloads](http://TYPAR.com/downloads) for full details.

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, **we make no warranties, express or implied, other than those warranties described in the TYPAR Weather Protection System Limited Warranty located online at [TYPAR.com/downloads](http://TYPAR.com/downloads), subject to the limitations and exclusions described therein.**



Made in USA. © 2017, Berry Plastics Corporation. TYPAR® is a registered trademark of Fiberweb, LLC, a wholly owned subsidiary of Berry Plastics Corporation. Please visit [TYPAR.com](http://TYPAR.com) for installation instructions and warranty information. Building Wraps | Flashings | Construction Tape

